



The Epson SureColor™ SC-S80670 is Epson's next generation, high-performance, eco-solvent signage printer. It incorporates the latest printing technologies, which include precision media feeding system and dual-performance PrecisionCore™ TFP printheads, to confidently meet the most demanding jobs. Equipped with the widest colour gamut in the new S-Series range, the SC-S80670 is set to astound with true-to-life colours in every brilliant printout.











ears Up to

Epson Genuine Inks

pson Environmenta uine Inks Friendly



Epson UltraChrome™ GS3 ink is Greenguard Gold certified and meets the French-VOC A+

Class criteria for low chemical emissions.



10 COLOURS 10 INKS MAX.						
	000	MAXIMUM	MAX. INK CAPACITY	PRECISIONCORE	PRINT SPEED	S SQM/HR
	ULTRACHROME GS3INK	MEDIA WIDTH	PER COLOUR	TFP PRINTHEAD	HIGH QUALITY**	PRODUCTION**
		64"	700ML*	DUAL	13.2	26.8

## **ENGINEERED FOR BUSINESS**

# **Outstanding Performance**

Print exceedingly vivid colours in outstanding quality with PrecisionCore technology and a wide colour gamut.

#### **Steadfast Reliability**

Tackle high-volume printing with ease through the newly developed precision media feeding system that allows you to print uninterrupted.

### **Optimised Design**

Enjoy hassle-free operations and maintenance with automatic media alignment and setup, along with automated printhead cleaning technology.







<sup>\* 700</sup>ml for all colours, 600ml for white, 350ml for metallic silver.

<sup>\*\*</sup> Based on 8-pass printing for high quality and 4-pass printing for production, on banner media.



1,338 mm

MODEL NUMBER		SC-S80670	SC-S80670		
SKU No.		C11CE45402	Dimensions & Weight SC-S80670		
Printer Width		64 "			
Printing Tec	hnology			— Weight: 284 kg (without ink)	
Print Head		PrecisionCore™ TFP ° Printhead			
Nozzle Configuration		360 x 1 x 2 nozzles each colour (x10)	(P20)		
Maximum Resolution		1440 x 1440 dpi	11111111	1 220	
Minimum In	nk Droplet Volume	4.2 pl			1,338 mr
Print Speed					-
1 Layer	Colour	Max Speed - 1 pass	Up to 95.1 m <sup>2</sup> /h (360 x 720 dpi)		
		High Speed - 2 pass (Billboard)	Up to 52.3 m <sup>2</sup> /h (720 x 720 dpi)		* *
		Production 1 - 4 pass	Up to 26.8 m <sup>2</sup> /h (720 x 720 dpi)	_	880 mm
		Production 2 - 6 pass	Up to 18.2 m <sup>2</sup> /h (720 x 720 dpi)	2,620 mm	2 000 111111
	Colour, Colour + White	High Quality - 8 pass	Up to 13.2 m <sup>2</sup> /h (720 x 720 dpi)		
		Max Quality 1 - 12 pass	Up to 8.8 m <sup>2</sup> /h (720 x 1440 dpi)	Ink Cartridge Compatibility	
		Max Quality 2 - 16 pass	Up to 6.8 m <sup>2</sup> /h (720 x 1440 dpi)	— ink cartriage compatibility	
		Max Quality 3 - 30 pass	Up to 3.7 m <sup>2</sup> /h (720 x 1440 dpi)	<ul> <li>Black (700 ml)</li> </ul>	C13T892100
	<del></del>	Max Quality 4 - 48 pass	Up to 2.4 m <sup>2</sup> /h (1440 x 1440 dpi)	- Cyan (700 ml)	C13T892200
	Colour + Metallic Silver	Production - 20 pass	Up to 4.2 m <sup>2</sup> /h (720 x 1440 dpi)	Magenta (700 ml)	C13T892300
	C 1	High Quality - 36 pass	Up to 2.3 m <sup>2</sup> /h (1440 x 1440 dpi)	Yellow (700 ml)	C13T892400
2 Layer	Colour + White	Speed - 18 pass	Up to 6.4 m <sup>2</sup> /h (720 x 720 dpi)	Light Cyan (700 ml)	C13T892500
		Production - 32 pass	Up to 3.5 m <sup>2</sup> /h (720 x 1440 dpi)	Light Magenta (700 ml)	C13T892600
	Calarina Martallia Cibran	High Quality - 48 pass	Up to 2.4 m <sup>2</sup> /h (1440 x 1440 dpi)	Light Black (700 ml)	C13T892700
	Colour + Metallic Silver	Production - 40 pass High Quality - 72 pass	Up to 1.9 m <sup>2</sup> /h (720 x 1440 dpi) Up to 1.1 m <sup>2</sup> /h (1440 x 1440 dpi)	Orange (700 ml)	C13T892800
3 Layer	Colour + White	Speed - 27 pass	Up to 3.2 m <sup>2</sup> /h (720 x 720 dpi)	• Red (700 ml)	C13T892900
3 Layer	Coloui + Wille	Production - 48 pass	Up to 1.7 m <sup>2</sup> /h (720 x 720 dpi)	○ White (600 ml)	C13T892A00
		High Quality - 72 pass	Up to 1.1 m <sup>2</sup> /h (1440 x 1440 dpi)	Metallic Silver (350 ml)	C13T892B00
Ink System			op to iii iii /ii(iiiio x iiiio api)		C151072500
Ink Type		Epson UltraChrome <sup>™</sup> GS3 Ink Technolo	pay with Red	Supplies & Optional Accessories	
Colours			k, Light Cyan, Light Magenta, Light Black, Orange, Red,		
Colouis		White or Metallic Silver	350 ml Cleaning Cartridge	C13T696000	
Ink Capacity		700 ml (all colours except White and Me	Maintenance Parts Kit	C13S210044	
Paper Handling		Rear roll feed (2 " / 3 " core with max 25	— Ink Cleaner	C13T699300	
Media Type		-	Cleaning Stick	C13S090013	
Printable Area		Max printing width: 1616 mm; Side Mar	Clean Room Wiper     Waste Ink Bottle	C13S090016 C13T724000	
Media Width		300 to 1626 mm			
Media Thickness		Up to 1 mm	Additional Print Drying System	C12C932381	
Heaters		Pre- and Platen- Heater (30 to 50 °C); Af	— Media Holding Guide	C12C932411	
Control Pan	el	2.7 " Colour LCD	2.7 " Colour LCD		
Connectivity	у				
Printer Inter	faces	Hi-Speed USB 2.0, 100BASE-TX / 1000BA	ASE-T		
Printer Lang	guages	Standard: ESC/P raster	Standard: ESC/P raster		
Printer Drive	ers				
Memory		512 MB main + 128 MB network			
Software		· ·	Standard: CD Installer, Communication Driver, EPSON Manuals Launcher, Operators Guides, General		
		•	d, EpsonNet Config, EpsonNet Setup, EpsonNet Print, Epson		
		Software Updater, Onyx RIPCenter			
Other Features		Auto Head Alignment Technology (Med	© 2017 Epson India Pvt. Ltd. All Righ	nts Reserved.	
		Report System, Custom Paper Backup		Reproduction in part or in whole, wi	ithout the written
	Operating Requirements		permission from Epson, is strictly prepared to the permission from Epson and Epson are prepared to the permission from Epson and Epson are prepared to the permission from Epson and Epson are prepared to the permission from Epson and Epson are prepared to the permission from Epson and Epson are prepared to the permission from Epson and Epson are prepared to the permission from Epson and Epson are prepared to the permission from Epson and Epson are prepared to the permission from Epson and Epson are prepared to the permission from Epson and Epson are prepared to the permission from Epson and Epson are prepared to the permission from Epson and Epson are prepared to the permission are prepared to the permission and Epson are prepared to the permission and Epson are prepared to the permission are prepared to the permission and Epson are prepared to the permission are prepared to the permission and the permission are prepared to the permission are prepared to the permission and the permission are prepared to the permission and the permission are prepared to the permission and the permission are prepared to t	rohibited. N are registered	
Power Requirements		Input voltage AC 100 - 240 V 50/60 Hz /	trademarks of Seiko Epson Corpora products names and other compan	ation. All other	
Power Consumption			Operating: Approx. 745 W; Standby: Approx. 445 W w/ heater ON; Sleep: Approx. 13 W;		
		Power Off: Less than 1.8 W		herein are for identification purpose the trademarks or registered traden	
	ded Operating	45 2505 20 2007 5117		respective owners. Epson disclaims	s any and all rights
	e & Humidity	15 - 35 °C; 20 - 80 % RH (non-condensin	g)	in those marks. Print samples show only. Specifications and product ava	vn are simulations
Printer Dime		2 (20 000 1 220		subject to change without notice ar	
Dimensions			2,620 x 880 x 1,338 mm (W x D x H) (storage)		
Weight			284 kg (without ink)		
Bundled Items			Substrate Support System (C12C932361), SC-S80670 Printer Starter Kit (include Onyx RIPCenter)		
Warranty		2-years limited warranty		<u> </u>	

Information correct as at February 2017.

### EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-30515000 Fax: 080-30515005

## **Regional Offices:**

Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Cochin - 4012 315, Coimbatore - 98942 19200, Jaipur 96808 52132, Kolkata - 6500 9370/77, Mumbai - 3079 8200, New Delhi - 3312 0300/01, Pune - 3028 6000/05, Hyderabad - 6463 9640/41



Dealer's Stamp